



Enviro-Clean 2000™ Biodegradable, Non-Toxic, Non-Hazardous Floor Cleaner

DESCRIPTION:

Enviro-Clean 2000 is an EDTA free and phosphate free hard surface cleaner especially formulated to be readily biodegradable, non-hazardous and non-toxic to personnel and the environment. For use on all hard surfaces especially floors and walls, **Enviro-Clean 2000** will remove oils, greases and all normal shop dirt and contaminants.

TYPICAL APPLICATIONS:

Enviro-Clean 2000 will perform exceptionally in mechanical floor scrubbers as well as manual mopping and scrubbing operations. For cleaning of walls and machine tool surfaces, **Enviro-Clean 2000** can be manually sprayed.

PERFORMANCE PROPERTIES:

Enviro-Clean 2000 contains detergents, chelating and sequestering agents which provide: quick penetration, dispersion and surface wetting. **Enviro-Clean 2000** is free rinsing for easier soil removal.

The liquid form of **Enviro-Clean 2000** makes it easier, safer, and more efficient to use than powder compounds. This eliminates the hazardous mixing of alkaline powders with water and it can be automatically metered to deliver a consistently accurate dilution.

RECOMMENDED USE DILUTIONS:

Dilute in water to suit the job. The quantity required depends on the quality and type of dirt, porosity of the surface, temperature, soak time allowed, and the method of application.

Recommended dilutions are:

For light duty shop soils such as cutting oils, coolants.....3 to 5% by volume.
For heavier dirt loads such as oils and greases..... 5 to 10% by volume.

USE TEMPERATURES AND TIME REQUIRED:

Many common soils can be removed "cold" at ambient temperatures. **Enviro-Clean 2000** is most effective at temperatures between ambient to 125°F. Some dirt is removed instantly on contact. The time required for equipment varies greatly. Additional time may be required for severe conditions. When speed is not important, energy to heat may be saved by extending the time.

Additional Information: Call Chempace at 1-800-423-5350



339 Arco Drive Toledo, OH 43607 • www.Chempace.com
419-535-0101 • 800-423-5350 • FAX 419-535-0531

Copyright 1999 Chempace Corporation

