

# TECHNICAL DATA SHEET

## FERROCOTE® 155 METAL PRESERVATIVE

FERROCOTE® 155 is a water-dispersed, synthetic corrosion preventive, offering comparable protection to some common oil-based products.

### Applications

Exhibiting a thin, nearly imperceptible film, FERROCOTE® 155 provides 2-4 months corrosion protection and offers an opportunity to incorporate a low VOC technology.

### Customers

- Motor Wheel

### Fluid Maintenance

Apply as received via immersion, flow-on, or slushing. Dilution of product is not recommended. Drying before packaging is recommended.

### Compatibility

To enhance process compatibility, use Quaker Houghton metalworking fluids and cleaners. Consult your Quaker Houghton representative.

### Benefits

- A single product to protect many metal surfaces (ferrous and non-ferrous) Protection = 20 Days (JAN-H-792 Humidity Cabinet)
- A water dispersed product, free of oil and solvent-based raw materials
- Easily cleaned with mild alkaline solutions
- Low VOC content

### Health, Safety and Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions. This product has a shelf life of 12 months, and it should be stored out of direct sunlight in temperatures between 40°F (4°C) and 100°F (38°C).

### Properties

PROPERTY	TYPICAL VALUE	UNIT
Appearance	Light yellow to white, cloudy fluid	
Pounds per gallon at 60°F	8.32	lbs/gal
Neat pH	9.6	

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 004235

