



## Auto Decant System

### Typical Applications

- Hydraulic Oil Reservoirs
- Lube Oil Reservoirs
- Quench Oil Reservoirs

### Equipment Specifications

- 2.5 GPM Flow Rate
- Feed Pump & Return Pump
- Electrical Controls, w/ "On" indicator
- 460V-3Ph-60Hz Power
- Bag Filter w/ 25 micron
- Inlet & Outlet hoses
- One Year Warranty
- Operating Manual w/ Spare Parts List

### Safety Features

- High Pressure Alarm
- Oil Tank Overflow Alarm
- OWS Overflow Alarm
- Disconnect Switch
- Strobe Alarm Light

The Auto Decant System is designed to automatically decant water from oil reservoirs. Fluid is pumped from the bottom of the reservoir into the system where it is filtered and separated using a series of chambers and gravity. The processed oil is pumped thru a filter to remove any remaining contaminants before going back into the oil reservoir. Waste water is discharged thru a separate line. The Auto Decant System can be run in a continuous or timed mode, 24/7.



## INDUSTRIAL FLUID SYSTEMS

22200 Ryan Road  
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

[www.industrialfluidsystems.com](http://www.industrialfluidsystems.com)